

BOSS 2



Black Frame/Smoke Lens
• 1651802



Frost Frame/Clear Lens
• 1651801



30 Grams

+ INNOVATIVE DUAL LENS DESIGN VIA A SINGLE GASKET



**+ CAN BE CONVERTED TO A FULLY APPROVED
PRESCRIPTION RX PRODUCT.**

**+ POLYCARBONATE FRAME ENSURES EXCELLENT
DURABILITY AND STRENGTH**

**+ RUBBER NOSE PADS/
TEMPLE TIPS**

bolle
SAFETY

BOSS 2

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
BOSS 2	 Black Frame/Smoke Lens	1651802	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Frost Frame/Clear Lens	1651801	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).

APPLICATIONS

- Assembly and production work
- Emergency response
- Driving
- Solar UV exposure
- Rigging
- High glare, outdoor work places

MAIN MARKETS

- Mining
- Transport
- Construction
- Local government/Councils
- Utilities
- Manufacturing

LENSES

- 2mm polycarbonate
- 'ALS' anti fog/anti-scratch coating on both sides of lens: Clear and Smoke
- 6 base curve lens
- 100% UV 385 – Clear
- 100% UV 400 – Smoke

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	No
FOAM	No
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz